



Accurate, Rugged

Ideal for long-term, unattended applications

Overview

The HMP60, manufactured by Vaisala, probe measures temperature for the range of -40° to 60°C, and relative humidity for the range of 0 to 100% RH. It is suitable for long-

term, unattended monitoring, and is compatible with all Campbell Scientific dataloggers.

Benefits and Features

- › Field-replaceable humidity chip eliminates recalibration downtime
- › Compatible with most Campbell Scientific dataloggers
- › Can be mounted to a tower/tripod mast or crossarm

Detailed Description

The HMP60 uses the INTERCAP capacitive RH chip. This chip is field-replaceable, which eliminates the downtime typically

required for the recalibration process.

Specifications

Supply Voltage	5 to 28 Vdc (typically powered by datalogger's 12 V supply)
Current Consumption	› 1 mA (typical) › 5 mA (maximum)
Filter Description	0.2 µm Teflon membrane
Settling Time	1 s
Housing Classification	IP65
Housing Material	AISI 316 stainless steel
Filter Cap Material	Chrome-coated ABS plastic
Field-Replaceable Chip or Recalibrate	Field-replaceable chip (RH only)

Sensor Diameter	1.2 cm (0.5 in.)
Filter Diameter	1.2 cm (0.5 in.)
Length	7.1 cm (2.8 in.)
Weight	0.05 kg (0.1 lb) with 1.83 m (6 ft) cable

Relative Humidity

Sensing Element	Vaisala's INTERCAP capacitive chip
Measurement Range	0 to 100% RH (non-condensing)
Typical Accuracy at -40° to 0°C	› ±5% (0 to 90% RH) › ±7% (90 to 100% RH)



Typical Accuracy at 0° to 40°C	<ul style="list-style-type: none"> » ±3% (0 to 90% RH) » ±5% (90 to 100% RH)
Typical Accuracy at 40° to 60°C	<ul style="list-style-type: none"> » ±7% (90 to 100% RH) » ±5% (0 to 90% RH)

Air Temperature	
Sensing Element	1000 ohm Platinum Resistance Thermometer (PRT)
Measurement Range	-40° to +60°C
Accuracy	±0.6°C