



CRS456V

Titanium Vented Water-Level Recording Sensor



Pressure Transducer Combined with a Recorder

High resolution and accuracy

Overview

The CRS456V consists of a submersible water-level and water-temperature sensor with its own time clock and memory to store the collected data—in a compact titanium case. This datalogging capability frees users to place the sensor in remote sites and let it collect data for long periods. HydroSci software is included and elegantly supports test setup, data

retrieval, and data display. Long battery life and rugged construction mean you can trust the CRS456V to collect important data. Low cost and ease of use make it a good choice in a variety of applications. The CRS451V is the same as this, but with a stainless-steel case.

Benefits and Features

- › Sensors and data-collection features in one instrument case
- › Rugged titanium case protects piezoresistive sensor allowing it to be used in saltwater and other harsh environments
- › Quality construction ensures product reliability
- › Fully temperature-compensated
- › Fast scan rate
- › Large data-storage capacity
- › Long battery life
- › Easy-to-use software

Detailed Description

The CRS456V has several pressure range options.

HydroSci software is available for [download](#). This software simplifies the process of configuring the CRS456V. Users can

configure the CRS456V to monitor surface water, ground water, or a standard pump test.

HydroSci software will display the data in tabular or graphical formats.

Specifications

Measurement Time < 1 s

Output Options

micro USB



Internal Data Collection Memory	4 MB
Logging/Scanning Modes	Standard, Delta, Wave, Logarithmic
Resolution	0.0035% FS
Dry Storage Temperature Range	-10° to +80°C WARNING: Sensor could be damaged if encased in frozen ice.
Operating Temperature Range	0° to 60°C WARNING: Sensor could be damaged if encased in frozen ice.
Overpressure	2 x pressure range
Power Requirements	Internal user-replaceable lithium battery
Battery Life	5+ years (when logging interval is once per hour; approximately 40,000 measurements)
Body Material	Titanium
Distance	<ul style="list-style-type: none"> › 2.54 cm (1 in.) Distance from black line etched on housing to end of NPT fitting › 2.3 cm (0.9 in.) Distance from black line etched on housing to end of standard nose cone › 9.9 cm (3.9 in.) Distance from black line etched on housing to end of weighted nose cone

Water-Level Accuracy	±0.1% full-scale-range TEB Includes the combined errors due to nonlinearity, hysteresis, nonrepeatability, and thermal effects over the compensated temperature range, per ISA S51.1.
Temperature Accuracy	±0.2°C
Diameter	2.22 cm (0.875 in.)
Length	22.23 cm (8.75 in.)
Weight	230 g (0.51 lb)

Power Consumption

Quiescent	< 80 µA
Measurement/ Communication	4 mA (1 s measurement)

Measurement Ranges at Fresh Water Depths

0 to 5.1 m (16.7 ft)	› 0 to 7.25 psi › 0 to 50 kPa
0 to 10.2 m (33.4 ft)	› 0 to 14.5 psi › 0 to 100 kPa
0 to 20.4 m (67 ft)	› 0 to 29 psi › 0 to 200 kPa
0 to 50.9 m (167 ft)	› 0 to 72.5 psi › 0 to 500 kPa
0 to 102 m (334.5 ft)	› 0 to 145 psi › 0 to 1000 kPa

For comprehensive details, visit: www.campbellsci.com.au/crs456v 

