



CS477-L

Radar Water-Level Sensor, 230 ft Maximum Distance



Non-Contact Water Level Monitoring

FCC approved for outdoor use

Overview

The CS477 is a radar-ranging sensor that monitors water level of rivers, lakes, tidal seas, and reservoirs. It can measure distances up to 70 meters. The CS477 outputs a digital SDI-12

signal to indicate distance and stage. This output can be read by many of our dataloggers.

Benefits and Features

- › FCC approved for outdoor use (FCC ID number MOIPULS616263)
- › Ideal for areas where submersed sensors can be damaged due to corrosion, contamination, flood-related debris, lightning, or vandalism
- › Compatible with most Campbell Scientific dataloggers
- › Low maintenance—no moving parts significantly reduces maintenance cost and time
- › Low power consumption
- › Rugged enough for harsh environments—NEMA rated 4X
- › Wide operating temperature range (-40° to +80°C)

Detailed Description

The CS477 emits short microwave pulses and then measures the elapsed time between the emission and return of the pulses. The elapsed time measurement is used to calculate the

distance between the sensor and the target (e.g., water, grain, slurry). The distance value can then be used to determine depth.

Specifications

| | | | |
|-------------------|--|----------------|---|
| Compliance | FCC approved for outdoor use (FCC IC number M01PULS616263) | Accuracy | ±15 mm (±0.6 in.) over entire measurement range |
| Measurement Range | 400 mm to 70 m (16 in. to 230 ft) | Resolution | 1 mm (0.04 in.) |
| | | Output Options | SDI-12 |

| | |
|-------------------------------|--|
| Radar Frequency | ~26 GHz |
| Electromagnetic Compatibility | Emission to EN 61326; Electrical Equipment Class B |
| Pulse Energy | 1 mW (maximum) |
| Beam Angle | 8° |
| Input Voltage | 9.6 to 16 Vdc |
| Surge Protection | 1.5 KVA |
| Temperature Sensitivity | <ul style="list-style-type: none"> › Average T_K is 2 mm/10 K › Maximum 5 mm (over the entire temperature range of -40° to +80°C) |
| Vibration Resistance | Mechanical vibrations with 4 g and 5 to 100 Hz |
| Housing Rating | NEMA 4x |

| | |
|-----------------------------------|---------------------------------|
| Housing Material | Aluminum, coated IP66/68 |
| Horn Material | 316L stainless steel |
| Typical Sleep Current Drain | 4.7 mA (with 12 V power supply) |
| Typical Measurement Current Drain | 14 mA (with 12 V power supply) |
| Side Cap Diameter | 8.6 cm (3.4 in.) |
| End Cap Diameter | 8.6 cm (3.4 in.) |
| Horn Diameter | 9.5 cm (3.7 in.) |
| Horn Length | 43.0 cm (16.9 in.) |
| Head Width | 13 cm (5 in.) |
| Total Length | 58.5 cm (23 in.) |
| Weight | 4.3 kg (9.4 lb) |

For comprehensive details, visit: www.campbellsci.com.au/cs477-radar-water-level 



Campbell Scientific Australia | 411 Bayswater Road | Garbutt, QLD 4814 | +61 (0)7 4401 7700 | www.campbellsci.com.au
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | USA

© 2018 Campbell Scientific, Inc. | 06/19/2018