



Overview

The ICEFREE3V vane is an electrically heated potentiometer wind-direction sensor designed for ice-prone sites. With an applied excitation voltage, a ratiometric dc voltage output is produced.

The ICEFREE3V is manufactured by Renewable NRG Systems and has an 8 m (26 ft) cable.

Detailed Description

The ICEFREE3V senses wind direction using a potentiometer. With the precision excitation voltage from the datalogger applied to the potentiometer element, the output signal is an analog voltage that is directly proportional to the azimuth of the wind direction.

- › Black - Reference
- › White - Signal
- › Shield - Shield

Red Cable

- › Black - Heater
- › White - Heater

Wiring Information

Gray Cable

- › Red - Excitation +

Specifications

Mechanical Range	360°
Electrical Range	352° (8° open)
Potentiometer Linearity	Within 1%
Potentiometer Resistance	0 to 10 kΩ
Operating Temperature Range	-40 to +80°C

Operating Humidity Range	0 to 100% RH
Supply Voltage	24 V ac/dc
Supply Current Inrush	8 A (maximum)
Supply Current Steady State	1 A at 20°C, 4 A under maximum thermal load (head frozen in clear ice then powered on)
Body Diameter	7.0 cm (2.75 in.)

Swept Diameter	21.2 cm (8.38 in.)
Center-to-Tail Radius	10.6 cm (4.19 in.)

Cable Length	8 m (26 ft)
Overall Assembly Height	23.9 cm (9.41 in.)
Weight	1.58 kg (2 lb)

For comprehensive details, visit: www.campbellsci.com.au/icefree3v 



Campbell Scientific Australia | 411 Bayswater Road | Garbutt, QLD 4814 | +61 (0)7 4401 7700 | www.campbellsci.com.au
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | USA

© 2018 Campbell Scientific, Inc. | 06/25/2018