



Wireless Network Link Interface

Powerful Wi-Fi Network Link and Access Point

Extremely low power consumption



Overview

The NL241 is a Wi-Fi WLAN (wireless local area network) interface that provides connectivity to your datalogger through your existing Wi-Fi network or any available Wi-Fi hotspot. It can either join an existing network or create a network providing a direct link to

Benefits and Features

- > Reduces power supply costs: NL241 has low power consumption
- Simplifies operation: Embedded radio transmitter allows the NL241 to be used as an access point (no more awkward ad hoc)
- Quickly configure the NL241 as an access point in the field: Surface button turns access point on and off

the datalogger or to a cloud data service, like Campbell Scientic's Konect. The NL241 can also be used as an access point for directly connecting to the datalogger from any Wi-Fi enabled device.

Datalogger Compatibility

The NL241 is compatible with all Campbell Scientific dataloggers; for specific limitation, refer to <u>www.campbellsci.com/nl241</u>. The NL241 is powered by the datalogger when connecting through

- > Access full PakBus routing capabilities
- > Communicate directly with the datalogger: IP connectivity is supported through LoggerLink smartphone app and LoggerNet PC software

the CS I/O port. When connected to the RS-232 port, a field cable (pn 14291) is used to connect the NL241 to an appropriate 12 Vdc power supply.



Ordering Information

Network Link Interface

NL241 Wi-Fi Communications Peripheral—shipped with an SC12 cable for connecting to the datalogger's CS I/O port, and hardware for mounting to an enclosure backplate

Accessories

- **15966** AC/DC adapter that can power the NL241 independently from an AC power outlet.
- **14291** Field power cable allows powering the NL241 from a 12 Vdc source.
- **10873** DB9 Female to DB9 Male Cable (6 feet)—connects the NL241 to the datalogger's RS-232 port
- 16005 Unity gain (0 dBd), 1/2 wave whip, omnidirectional antenna.

The 16005 antenna features an articulating knuckle joint for easy orientation, weatherized jacket for outdoor applications, and internal counterpoise for ground plane independence.

Specifications

- Material: Aluminum case with black anodized finish
- > Operating Temperature Range: -40° to +70°C
- Dimensions: 16 x 7.3 x 2.54 cm (6.3 x 2.9 x 1 in)
- Weight: 180.35 g (6.36 oz)
- Configuration: Device Configuration Utility over USB or Wi-Fi Telnet console over Wi-Fi Terminal menu over RS-232
- CS I/O Port: SDC 7, 8, 10, or 11 (does not support ME); 9600 to 460.8k bps
- RS-232 Port: DTE, DB9 Male; 1200 to 115.2k bps
- **)** USB Port: Micro-B
- Supported Protocols: IPv4, IPv6, ICMP/Ping, ICMPv6/Ping, TCP/IP, DHCP Client, DHCP Server (in access point mode only), SLAAC, DNS Client, HTTPS Proxy, TLS, Telnet Server, PakBus®, Modbus
- TCP Connections: 50 simultaneous connections supported; 10 of the 50 TCP connections can be used for TLS
- > PakBus® Router: 50 routes supported
- Modbus Server: up to 15 concurrent transactions supported

WLAN

- Antenna Connector: RPSMA
- Supported Technologies: 802.11b/g/n, WPA/WPA2-Personal, WPA/WPA2-Enterprise Security
 WEP Client Mode: WPA/WPA2-Personal and Enterprise
 WEP Access Point Mode: WPA2-Personal

- Communication Rate 802.11b: up to 11Mbps 802.11g: up to 54 Mbps 802.11n: up to 72 Mbps
- Transmit Power: 7 to 18 dBm (5 to 63 mW)
- > Rx Sensitivity: -97 dBm
- Frequency: 2.4 GHz

Power

- CS I/O or DC Barrel Connector (not USB)
- Supply Voltage: 9 to 16 Vdc
- Power Consumption Client Mode: 7.5 to 8 mA idle, 65 to 75 mA communicating Access Point Mode: 67 mA idle, 70 mA communicating Standby: less than 1.5 mA

Compliance Information

- > CE Compliant
- Complies with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules.
- Embedded Radio Transmitter Approvals FCC Identifier: XF6-RS9113SB Industry Canada: 8407A-RS9113SB
- View EU Declaration of Conformity documentation at: <u>www.campbellsci.com/nl241</u>



 CAMPBELL
 Campbell Scientific, Inc.
 815 W 1800 N
 Logan, UT 84321-1784
 (435) 227-9120
 www.campbellsci.com

 SCIENTIFIC
 USA | AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | SE ASIA | SOUTH AFRICA | SPAIN | UK

© 2017 Campbell Scientific, Inc. July 20, 2017