



## OBS-3+ Turbidity Sensor



## Accurate, Rugged

Compact, low-power probe is field-proven

### Overview

The OBS-3+ is a submersible turbidity probe that has sideways-facing optics. It uses OBS technology to measure suspended solids and turbidity for applications ranging from water quality

in freshwater rivers and streams to sediment transport and dredge monitoring. Campbell Scientific dataloggers measure the OBS-3+ probe's output and calculate turbidity.

### Benefits and Features

- › Sideways facing optics avoid obstructions above and below the probe
- › Measures suspended solids and turbidity for up to 4000 NTUs
- › Provides a compact, low-power probe that is field proven
- › Compatible with most Campbell Scientific dataloggers
- › Accurate and rugged
- › Stainless-steel body allows use down to 500 m in fresh water
- › Titanium body allows use down to 1500 m in fresh or salt water
- › Fitted with MCBH-5-FS, wet-pluggable connector—multiple mating cable length options available
- › Offers an optional five-point sedimentation calibration for better measurements (see Ordering Info on the web page)

### Detailed Description

The OBS-3+ uses its sideways-facing optics to emit a near-infrared light into the water. It then measures the light that bounces back from the water's suspended particles.

If an obstruction is in the emitted light's range, the light will scatter back and the turbidity reading will be too high. This

probe's sideways-facing optics avoids obstructions above and below the probe. The OBS300 is available for locations that have obstructions around the sides of the probe.

*OBS® is a registered trademark of Campbell Scientific.*

## Specifications

Maximum Submersion Depth	<ul style="list-style-type: none"> <li>› 500 m (1640.5 ft) for stainless-steel body</li> <li>› 1500 m (4921.5 ft) for titanium body</li> </ul>
Concentration Accuracy	<ul style="list-style-type: none"> <li>› 2% of reading or 1 mg/l (whichever is larger) for mud</li> <li>› 4% of reading or 10 mg/l (whichever is larger) for sand</li> </ul>
Maximum Concentration Range	<ul style="list-style-type: none"> <li>› <i>Maximum concentration depends on sediment size, particle shape, and reflectivity.</i></li> <li>› 5,000 to 10,000 mg/l (for mud)</li> <li>› 50,000 to 100,000 mg/l (for sand)</li> </ul>
Operating Temperature Range	0° to 40°C
Drift over Time	< 2% per year
Maximum Data Rate	10 Hz
Minimum Warm-up Time	2 s
Infrared Wavelength	850 nm ±5 nm
Daylight Rejection	-28 dB (re: 48 mW/cm <sup>2</sup> )
Optical Power	2000 μW
Turbidity Accuracy	2% of reading or 0.5 NTU (whichever is larger)

Housing Material	316 stainless steel or titanium
Connector	MCBH-5-FS, wet-pluggable
Diameter	2.5 cm (0.98 in.)
Height	14.1 cm (5.56 in.)
Weight	181.4 g (0.4 lb)

### -2.5 Output Option

Output Voltage	0 to 2.5 V (over selected NTU range)
Supply Voltage	5 to 15 Vdc
Current Drain	15 mA

### -5 Output Option

Output Voltage	0 to 5 V (over selected NTU range)
Supply Voltage	5 to 15 Vdc
Current Drain	15 mA

### -20 Output Option

Output Voltage	4 to 20 mA (over selected NTU range)
Supply Voltage	9 to 15 Vdc
Current Drain	45 mA

For comprehensive details, visit: [www.campbellsci.com.au/obs-3plus](http://www.campbellsci.com.au/obs-3plus) 



Campbell Scientific Australia | 411 Bayswater Road | Garbutt, QLD 4814 | +61 (0)7 4401 7700 | [www.campbellsci.com.au](http://www.campbellsci.com.au)  
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | USA

© 2018 Campbell Scientific, Inc. | 06/26/2018