



Overview

The RF412 is a high-speed 900 MHz serial radio designed for unlicensed operation in several countries, including Australia and New Zealand. The RF412 is a 915 to 928 MHz frequency-hopping spread-spectrum radio with a configurable transmit-power output of 5 to 250 mW and software-selectable channel masking for improved RF interference immunity. This power-sipping, yet speedy, radio provides a cost-effective way to network dataloggers.

The RF412 is part of the RF407-series of radios that includes:

- ▶ **RF407:** North America (FCC & IC), 902 to 928 MHz
- ▶ **RF412:** Australia (ACMA RCM), 915 to 928 MHz
- ▶ **RF422:** Most of Europe and some of Asia (ETSI), 863 to 870 MHz
- ▶ **RF427:** Brazil (ANATEL), 905/920 MHz

Note to RF411A users: The RF411A is factory upgradeable to an RF412. Contact Campbell Scientific for a [Returned Material Authorization \(RMA\)](#).

Benefits and Features

- ▶ Does not require individual operational license in Australia or New Zealand
- ▶ High-speed serial communication, optimized for PakBus networks
- ▶ Low power (< 2 mA idle) during periods of inactivity
- ▶ Supports point-to-point with RF retries and point-to-multipoint operations
- ▶ Remote diagnostics using PakBus node operations

Specifications

Radio Type	Frequency Hopping Spread Spectrum (FHSS)	Channel Capacity	Eight 25-channel hop sequences sharing 31 available channels
Frequency	915 to 928 MHz	Data Rate	200 kbps
Power Output	5 to 250 mW (software-selectable)	Link Throughput	105 kbps (maximum)
Receiver Sensitivity	-101 dBm	Antenna Connector	Reverse Polarity SMA (RPSMA) jack

LEDs	Red TX/PWR and green RX
RS-232 Baud Rate	1200 to 115200 bps
CS I/O Modes	SDC 7, 8, 10, 11, and ME master
Operating Temperature Range	-40° to +70°C
Power	9 to 16 Vdc
Power Connector	2.5 mm DC power jack
Average Current Drain	<ul style="list-style-type: none"> › Transmit: < 80 mA (250 mW TX Power) › Receive: 15 mA › Stand-by: < 0.5 mA (depending on power saving mode)
Communication Ports	<ul style="list-style-type: none"> › RS-232 9-pin D female › CS I/O 9-pin D male › USB Type B jack
Dimensions	11.1 x 6.9 x 2.7 cm (4.4 x 2.7 x 1.1 in.)

Dimension are from the tip of the antenna connector to the other side of the case, and from the bottom of the case to the top of the DB9 connector jack screw. The width includes the thickness of the screw heads on the screws that hold the case together.

Weight	<ul style="list-style-type: none"> › 136 g (4.8 oz) without "Ships With" items › 283.5 g (10 oz) with "Ships With" items
--------	--

Certifications

Australia	ACMA RCM
United States (FCC Part 15.247)	MCQ-XB900HP
Industry Canada (IC)	1846A-XB900HP

For comprehensive details, visit: www.campbellsci.com.au/rf412



Campbell Scientific Australia | 411 Bayswater Road | Garbutt, QLD 4814 | +61 (0)7 4401 7700 | www.campbellsci.com.au
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | USA

© 2018 Campbell Scientific, Inc. | 06/26/2018