



A Market-Leading, Analog, Ambient Air Temperature Sensor

Easy to use

Overview

The TempVue™10 represents the next generation of air-temperature measurement sensors, meeting all relevant World Meteorological Organization (WMO) temperature recommendations.

Designed with the customer in mind, the TempVue 10 easily interfaces with Campbell Scientific or third-party data loggers and fits a wide range of passive solar radiation shields. The sensor comes with a short, attached cable and terminates with an M12 connector, which provides exceptional convenience, environmental protection, and data integrity for use in a variety of applications.

Benefits and Features

- › Meets WMO step change response time at 1 m/s (3.28 ft/s)
- › Maintains high measurement stability over both time and temperature
- › Incredibly easy to install or remove for calibration checks
- › Highly durable, providing sensor element protection in even the harshest environmental conditions
- › Able to be wired with a two-, three-, or four-wire Platinum Resistance Thermometer (PRT) configuration
- › Allows for cable length adjustments without the need for calibration changes
- › Includes calibration certificate

Detailed Description

The sensor consists of a wire-wrapped, four-wire Pt100 Resistance Temperature Detector (RTD) element encapsulated in an epoxy-filled, stainless-steel housing. The thin yet robust housing, combined with the Pt100 sensing element, provide the first true WMO-compliant sensor to

meet the 20-second step response time with an ambient wind speed of only 1 m/s (3.3 ft/s).

The TempVue 10 has a maximum measurement uncertainty of only 0.3°K over the entire measurement range of -80° to +60°C, with only 0.1°K over the most common temperature range of -40° to +40°C.

Specifications

| | | |
|--------------------|---------------------|---------------------|
| Sensor Description | Platinum Resistance | Thermometer (Pt100) |
|--------------------|---------------------|---------------------|



Measurement Uncertainty $\gg \pm 0.3^{\circ}\text{K}$ over -80° to $+60^{\circ}\text{C}$
(-112° to $+140^{\circ}\text{F}$) range
 $\gg \pm 0.1^{\circ}\text{K}$ over -40° to $+40^{\circ}\text{C}$ (-40°
to $+104^{\circ}\text{F}$) range

Temperature Measurement Range -80° to $+60^{\circ}\text{C}$ (-112° to $+140^{\circ}\text{F}$)

Time Constant in Air 20 s for a wind speed of 1 m/s
(3.3 ft/s)

Resolution Three decimal places (0.001°C)

Connector Type M12 (to extend beyond 1 m [3
ft] standard cable length)

Probe Diameter 1.9 cm (0.75 in.) maximum

Probe Length 12.1 cm (4.75 in.) tip to end of
cable gland

Extended Probe Length 18.1 cm (7.125 in.) tip to end of
extender piece

Total Length 97.16 cm (38.25 in.) tip to end of
connector

Weight 70 g (0.15 lb) for probe with
extender piece, including
standard 1 m (3 ft) cable with
M12 connector

For comprehensive details, visit: www.campbellsci.com.au/tempvue10 



Campbell Scientific Australia | 411 Baywater Road | Garbutt, QLD 4814 | +61 (0)7 4401 7700 | www.campbellsci.com.au
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2023 Campbell Scientific, Inc. | 07/31/2023