



WINDSONIC4-L

2-D Sonic Wind Sensor with SDI-12 Output



No Moving Parts

Minimizes routine maintenance costs

Overview

The WindSonic4 is a two-dimensional ultrasonic anemometer for measuring wind direction and speed. It provides an alternative to traditional mechanical cup and vane or propeller and vane anemometers. This sonic wind sensor outputs an SDI-12 signal that can be read a CR200(X)-series, CR510, CR10X, CR800, CR850, CR1000, CR3000, or CR5000 datalogger.

The Windsonic4 is not recommended for conditions where rime, ice, or horizontal snow will occur. This sensor is not heated. Please contact Campbell Scientific for information on a heated 2-D sonic anemometer that will work in these conditions.

Benefits and Features

- › Low maintenance—no moving parts significantly reduces maintenance cost and time
- › Provides a minimum detectable wind speed of 0.01 meters per second
- › Compatible with most Campbell Scientific dataloggers

Detailed Description

The WindSonic4 uses two pairs of orthogonally oriented transducers to sense the horizontal wind. The transducers bounce the ultrasonic signal from a hood, thus minimizing the effects of transducer shadowing and flow distortion.

Unlike mechanical anemometers, the WindSonic4 has no moving parts to be periodically replaced—minimizing routine maintenance costs.

Specifications

Operating Humidity Range < 5% to 100% RH

Operating Temperature Range -35° to +70°C

Storage Temperature Range -40° to +80°C (typical)

Input Voltage 9 to 30 Vdc

Typical Current Drain < 10 mA (@12 V)

Measurement Frequency 40 Hz block averaged to a 1 Hz output frequency

Outputs Parameters	Polar (direction and speed) or orthogonal (U_x and U_y wind)
Output Signal	SDI-12 version 1.3
Diameter	14.2 cm (5.6 in.)
Length	16.0 cm (6.3 in.)
Weight	0.5 kg (1.1 lb)

Maximum Cable Length

-NOTE-	<i>For longer cable lengths, contact Campbell Scientific.</i>
1 Sensor Connected to 1 Port	91.44 m (300 ft)

2 to 10 Sensors Connected to 1 Port 60.91 m (200 ft)

Wind Direction

Range	0° to 359° (no dead band)
Accuracy	$\pm 3^\circ$
Resolution	1°

Wind Speed

Range	0 to 60 m/s
Accuracy	$\pm 2\%$ (@ 12 m/s)
Resolution	0.01 m/s

For comprehensive details, visit: www.campbellsci.com.au/windsonic4



Campbell Scientific Australia | 411 Bayswater Road | Garbutt, QLD 4814 | +61 (0)7 4401 7700 | www.campbellsci.com.au
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | USA

© 2018 Campbell Scientific, Inc. | 06/27/2018