



## ClariVue 20

ISO 7027-Compliant, Side-Scatter Turbidity Sensor



## Titanium Housing for Harsh Environments

Offering analog, Modbus, and SDI-12 communications

### Overview

The ClariVue™20 is an ISO 7027-compliant, submersible, 90-degree, side-scatter turbidity sensor in a rugged titanium housing, making it the ideal choice for highly corrosive environments. The side-scatter turbidity measurement can be

used as a surrogate for suspended sediment concentration (SSC) in aquatic ecosystems. The sensor returns data via SDI-12, analog, or Modbus to a data logger or controller for easy integration into your new or existing system.

### Benefits and Features

- › Accurate measurement of suspended solids and turbidity to the industry standard 4000 FNUs
- › Field-proven performance and reliability in a compact, low-power probe
- › Compatible with modern Campbell Scientific data loggers and third-party systems
- › Titanium housing for long-term deployment in the harshest of environments
- › Wet-mateable connector allows for flexible installation without the worry of water ingress

### Detailed Description

The ClariVue 20 is designed to operate in fresh and saline environments. The sensor face is made from titanium to slow biological growth over the optical windows; however, the

sensor requires regular maintenance to keep the optical window clean in high bio-fouling environments.

**Caution:** The ClariVue 20 may become damaged if it is encased in frozen liquid.

### Specifications

Standards

Meets ISO 7027-1:2016 (side scatter) standard for turbidity

measurements



Signal Type	SDI-12 v1.4, Modbus through RS-485, or analog
Operating Temperature Range	-2° to +40°C (28° to 104°F)
Analog Signal Output	0 to 1 Vdc
Power Requirements	9.6 to 18 Vdc
Measurement Range	0 to 4000 FNU
SDI-12 Measurement Response Time	12 to 28 s depending on the SDI-12 command (Refer to the manual for more information.)
Resolution	0.2 FNU
Particle Size	0.1 to 0.5 µm
Accuracy	±2% or 0.5 FNU, whichever is greater
Housing Material	Titanium
Head Material	Titanium

Optics	Sapphire lens
Connector Description	MCBH-5-FS, titanium, six gold-plated pins, wet-mateable
Cable Type	Six-conductor, polyurethane jacket with water block
Optical Assembly	Sealed with double O-rings
Internal Temperature Measurement	±0.2°C (±0.4°F) accuracy
Maximum Depth	500 m (1,640 ft)
Sensor Diameter	3.0 cm (1.2 in.)
Sensor Length	16.6 cm (6.5 in.)
Sensor Weight	200 g (0.44 lb)

### Power Consumption

Initial Measurement	32 mA (30 s)
Idle	0.75 mA
Measurement	32 mA

For comprehensive details, visit: [www.campbellsci.ca/clarivue20](http://www.campbellsci.ca/clarivue20) 



Campbell Scientific (Canada) Corp. | 14532 131 Avenue NW | Edmonton AB T5L 4X4 | 780.454.2505 | [www.campbellsci.ca](http://www.campbellsci.ca)  
 AUSTRALIA | BRAZIL | [CANADA](#) | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA