



Detects onset of snowfall and snowmelt

Proven performance and field tested

Overview

The SDMS-40 is a powerful and cost-effective 2D multipoint, laser based snowfall sensor. In the past, multipoint laser based snow depth sensors have typically been complex and costly, so the practical SDMS-40 was developed to address those issues. Performance and reliability of the device has been proven with thorough testing of the sensor and its measurement method (read the white paper). With the SDMS-40, you can enjoy accurate data from a compact, automated, multipoint scanning laser snow depth sensor at a reasonable price.

The ability to quickly and reliably detect the onset of snowfall and snowmelt is a highly sought after feature in a snow depth

sensor, and the SDMS-40 does not disappoint. It is one of a few laser sensor models available in the world that can reliably detect the onset of snowfall and snowmelt, and of all the models available, the SDMS-40 is the most cost-effective. Campbell Scientific prides itself on the high quality and accuracy of its products. We won't put our stamp of approval on anything that does not meet our expectations or the needs of our clients, and we want to ensure you can trust the quality and accuracy of the SDMS-40 like you would trust any Campbell system. So we field tested the SDMS line of snow sensors over three Canadian winter seasons. It has proven itself to be practical, accurate, and of excellent quality.

Benefits and Features

- › Detects the onset of snowfall or snowmelt quickly and reliably
- › Proven performance by field tests over three winter seasons from 2013 to 2015
- › Allows easy installation on poles, building walls, or any structure
- › Can be used as an additional gauge to existing weather stations
- › Compact and light gauge structure
- › Less sensitive to ground conditions
- › Filters out noise input caused by obstacles and abnormal situations
- › Can operate on natural ground and different types of snow plates

Specifications

General

Target Area Diameter	30 cm – 200 cm depending on installation height
Beam Half-Angle	7°
Snow Depth Measurement Method	Multipoint laser scanning
Number of scanning points	36
Ground target	available as an option
Range	1-5 meters
Gauge Pointing Angle	0 to 45°
Accuracy	±3 mm
Resolution	1 mm
Operational Temperature Range	-40 to 50°C
Power Supply Requirements	12-15 VDC, 2 A

Enclosure Classification	IP68
Laser Classification	2
Dimensions	12cm x 28cm x 10cm
Weight	approx. 1.8kg
RoHS	Compliant

Current Draw

Standby	50 mA
During Measurement	300 mA
During Measurement with Heater	360 mA
Heater B	1.2 A

Interfaces

Communication Interfaces	RS-232, RS-485, SDI-12
Maximum Baud Rate	57.6 (RS-232 and RS-485)

For comprehensive details, visit: www.campbellsci.ca/sdms-40 



Campbell Scientific (Canada) Corp. | 14532 131 Avenue NW | Edmonton AB T5L 4X4 | 780.454.2505 | www.campbellsci.ca
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | USA

© 2017 Campbell Scientific (Canada) Corp. | 10/03/2017