



Reliable, Accurate Wind Speed

Compatible with all Campbell Scientific dataloggers

Overview

The 014A, manufactured by Met One, is a three-cup anemometer that monitors wind speed for the range of 0 to 45 m/s with a threshold of 0.45 m/s. It connects directly to a

Campbell Scientific datalogger, which measures the 014A's pulse signal and converts the signal to engineering units (mph, m/s, knots).

Benefits and Features

- › Ideal for applications that do not require wind direction measurements
- › Sealed magnetic reed switch
- › Designed for continuous, long term, unattended operation in adverse conditions
- › Standard aluminum cup assembly has a distance constant of less than 4.5 m
- › For greater sensitivity, an optional LEXAN cup assembly has a distance constant of less than 1.5 m

Technical Description

The 014A is constructed of corrosion-resistant, stainless-steel and anodized aluminum. Its three-cup anemometer assembly contains a sealed magnetic reed switch. Rotation

of the cupwheel produces a pulse that is directly proportional to wind speed.

Specifications

Sensor	3-cup anemometer
Measurement Description	Wind speed
Range	0 to 45 m/s (0 to 100 mph)
Starting Threshold	0.45 m/s (1.0 mph)
Accuracy	0.11 m/s (0.25 mph) or 1.5%
Contact Rating	10 mA (maximum)
Operating Temperature Range	-50° to +70°C

Distance Constant	› < 4.5 m (15 ft) standard › < 1.5 m (5 ft) optional fast response
Cable Description	Quick-connect connector with vinyl jacketed, shielded cable
Radius	10.4 cm (4.1 in.)
Height	34.8 cm (13.7 in.)
Sensor Weight	318 g (11 oz)

Cable Weight

140 g (5 oz) per 3 m (10 ft)

length

For comprehensive details, visit: www.campbellsci.eu/014a 



80 Hathern Road, Shepshed, LE12 9GX UK | +(0)1509 828888 | sale@campbellsci.co.uk | www.campbellsci.eu
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2020 Campbell Scientific, Ltd. | 07/02/2020