



Rugged, Accurate, Versatile

Can be used in a variety of applications

Overview

The 109SS is a rugged, accurate probe that measures soil or water temperature from -40° to +70°C. It is especially suited

for harsh, corrosive environments, and can be easily interfaced with our dataloggers.

Benefits and Features

- › Designed for harsh, corrosive environments
- › Fast response time
- › Wide temperature measurement range
- › Easy to install or remove
- › Compatible with most of our current and retired data loggers

Technical Description

The 109SS consists of a thermistor encased in a sheath made from grade 316 stainless steel. The rugged stainless-steel sheath protects the thermistor allowing the 109SS to be

buried or submerged in harsh, corrosive environments. This probe also has a fast time response.

The 109SS's thermistor can survive temperatures up to 100°C, but the overmolded joint and cable should not be exposed to temperatures hotter than +70°C.

Specifications

Output	Analog
Operating Temperature Range	-40° to +70°C
Accuracy	› <i>Note:</i> Overall probe accuracy is a combination of thermistor interchangeability, bridge-resistor accuracy, and error of the Steinhart-Hart equation. Interchangeability is the principle component error. If

needed, an estimate of the interchangeability error for 0 to 50°C, that can be used as the *Offset* parameter of the **Therm1090** instruction, can be determined with a 1-point or 2-point calibration.

- › ±0.60°C (-40 to +70°C)
- › ±0.49°C (-20 to +70°C)

Maximum Submergence	45.7 m (150 ft) or 434 kPa (63 psi)
Temperature Measurement Range	-40° to +70°C
Thermistor Temperature Survival Range	-50° to +100°C
Overmolded Joint and Cable Temperature Survival Range	-50° to +70°C
Interchangeability Error	<ul style="list-style-type: none"> › ±0.1°C tolerance (25°C) › ±0.38°C tolerance (0°C) › ±0.3°C tolerance (50°C) › ±0.4°C tolerance (70°C) › ±0.6°C tolerance (-40°C)
Steinhart-Hart Equation Error	≤ 0.02°C (-40°)
Time Constant in Air	› 0.5 s (antifreeze/water rolling)

	<ul style="list-style-type: none"> › 7.5 s (air @ 3 m/s) › 31 s (still air)
Sensor Description	Micro-BetaCHIP Probe 10K3MCD1, 0.5 mm (0.018 in.) diameter, 10 kohm at 25°C
Cable Description	0.56 cm (0.22 in.) diameter with Santoprene jacket
Cable/Probe Connection	"ATUM" heat shrink, "Macromelt" overmolded joint
Stainless-Steel Sheath Diameter	0.16 cm (0.063 in.)
Stainless-Steel Sheath Length	5.84 cm (2.3 in.)
Overmolded Joint Diameter	1.02 cm (0.40 in.)
Overmolded Joint Length	4.24 cm (1.67 in.)
Weight	0.1 kg with 3.2 m cable (0.2 lb with 10.5 ft cable)

For comprehensive details, visit: www.campbellsci.eu/109ss 



80 Hathern Road, Shepshed, LE12 9GX UK | +(0)1509 828888 | sale@campbellsci.co.uk | www.campbellsci.eu
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA