



Portable Memory

Adds CompactFlash capability
to dataloggers

Overview

The CFM100 stores the datalogger's data on a removable CompactFlash (CF) card. The CFM100/CF card combination can be used to expand the datalogger's memory, transport

data/programs from the field site(s) to the office, and upload power up functions. The module connects to the 40-pin peripheral port on a CR1000 or CR3000 datalogger.

Benefits and Features

- ▶ Used to expand data storage of our CR1000 and CR3000 dataloggers
- ▶ Connects to the data logger's peripheral port
- ▶ Small, light-weight CF cards fit in your pocket for easy transport between the data logger and PC

Technical Description

The CFM100 includes a card slot that can fit one Type I or Type II CF card. Only industrial-grade CF cards should be used with our products. Although consumer-grade cards cost less than industrial-grade cards, the consumer-grade cards are more susceptible to failure resulting in both the loss of the card and its stored data. Industrial-grade cards also function over wider temperature ranges and have longer life spans than consumer-grade cards.

Data stored on the card can be retrieved either by removing the card and carrying it to a computer or through a communications link with the datalogger. The computer can read the CF card either with the computer's PCMCIA slot and the CF1 adapter or the computer's USB port and the 17752 Reader/Writer.

CardConvert is used to convert and save binary data from a CompactFlash card. CardConvert is included in our PC200W, PC400, LoggerNet, and RTDAQ datalogger support software.

Software Requirements

- ▶ LoggerNet version 3.1.3 or later
- ▶ PC400 version 1.2.1 or later

Datalogger Operating System (OS) Requirements

The CR1000 OS must be OS 4 or later. Both the CR1000 and CR3000 need OS 25 or later to read cards with more than 2 GB of storage.

Specifications

Storage Capacity 256 MB, 2 GB, or 16 GB

Typical Access Speed 200 to 400 kbits s⁻¹

Memory Configuration	User selectable; ring (default) or fill-and-stop
Power Requirements	12 V supplied through the data logger's peripheral port
CF Card Requirements	Industrial-grade
Temperature Range	<ul style="list-style-type: none"> › -55° to +85°C (extended) › -25° to +50°C (standard)
Dimensions	› 25.2 x 10.2 x 7.1 cm (9.9 x 4.0 x 2.8 in.) of CR1000 with CFM100 attached

› 10.0 x 8.3 x 6.5 cm (4.0 x 3.3 x 2.6 in.)

Weight 133 g (4.7 oz)

Typical Current Drain

RS-232 Port Active	<ul style="list-style-type: none"> › 30 mA (writing to card) › 20 mA (reading card)
RS-232 Port Not Active	<ul style="list-style-type: none"> › 15 mA (reading card) › 20 mA (writing to card)
Low Power Standby	700 to 800 μ A

For comprehensive details, visit: www.campbellsci.eu/cfm100 



80 Hathern Road, Shepshed, LE12 9GX UK | + (0)1509 828888 | sale@campbellsci.co.uk | www.campbellsci.eu
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2020 Campbell Scientific, Ltd. | 06/22/2020