



Low cost – entry level sensor

Overview

The Kalyx-RG is our recommended solutions for scientists and professionals on a limited budget but who still require scientific standard rain data. The gauge is based on the

physical size of the traditional 127 mm (5") Met Office rain gauge and has a unique aerodynamic profile.

Benefits and Features

- › Low Cost - Entry level sensor
- › Can be pole mounted
- › Comparable results to full-size gauge such as ARG100
- › Compact and lightweight

Technical Description

The Kalyx-RG has a standard low density plastic tipping bucket adjusted to 0.2 mm resolution and is produced from UV stabilised external materials.

Traditional cylinder-shaped rain gauges are inaccurate due to the effect of wind blowing over the orifice. The physical

presence of the gauges causes air to accelerate, carrying rainfall away from the collecting vessel. The effect of this can be up to a 20% reduction in rainfall catch. The unique aerodynamic shape of this range of scientific standard rain gauges reduces this effect, ensuring a high level of confidence in the accuracy of your measurements.

Specifications

Tip sensitivity	0.2 mm rain per tip
Output	Contact closure (reed switch)
Typical Accuracy	98% at 20 mm/hr 96%+ at 50 mm/hr 95%+ at 120 mm/hr (above 120 mm/hr we recommend mathematical correction - contact CSL)
Rainfall intensity	Up to 1000 mm/hr (with mathematical correction - contact CSL)

Colour	White
Dimensions	
Height - max (with baseplate)	245 mm
Funnel diameter	127 mm (5")
Funnel Area	12,668 mm ²
Weight	700 g (without baseplate) 1 Kg (with baseplate)

Height (no baseplate) 225 mm

For comprehensive details, visit: www.campbellsci.eu/kalyx-rg 



**CAMPBELL
SCIENTIFIC**

80 Hathern Road, Shepshed, LE12 9GX UK | +(0)1509 828888 | sale@campbellsci.co.uk | www.campbellsci.eu
UK | AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | USA

© 2019 Campbell Scientific, Ltd. | 08/23/2019