



## Simple and Robust Digital Sensor

### Overview

The RainVUE™20 is ideal for many hydrological or meteorological applications such as weather stations and flood warning systems. The RainVUE™20 is an SDI-12 tipping bucket rain gage in the RainVUE family of products. Advanced algorithms and digital processing within the sensor compensate for errors caused by high-intensity rain and provide accurate precipitation and intensity

measurements. Constructed of an aerodynamic powder-coated aluminum funnel, the RainVUE™20 is robust and minimizes the amount of liquid precipitation that is lost due to the effects of wind. This rain gage offers the user flexibility with the option to select from a series of set cable lengths or a user-defined cable length.

### Benefits and Features

- ▶ Powder-coated aluminum bucket suitable for all environments
- ▶ Extremely robust and versatile for applications where data precision and accuracy are critical
- ▶ Unique aerodynamic shape to minimize wind effects and increase accuracy
- ▶ Measures precipitation intensity up to 1500 mm/h (60 in./h)
- ▶ Meets WMO recommendations for funnel area
- ▶ Digital processing corrects for high-intensity precipitation errors up to 1500 mm/h (60 in./h)
- ▶ Tilt measurement for remote diagnostics on the sensor
- ▶ Internal temperature measurement
- ▶ Easy leveling with external leveling bubble
- ▶ Adjustable mounting feet to simplify leveling

### Technical Description

The RainVUE™20 funnels rainfall through a stainless-steel gauze filter that traps and removes debris. The rainfall flows through a nozzle into one of the two halves of the tipping bucket. The internal tipping bucket assembly rotates around precision, rolling pivot bearings, it tips when the first bucket fills to a fixed calibrated level, and then the balance arm moves the second bucket under the funnel. A magnet attached to the balance arm actuates a reed switch as the bucket tips.

The aerodynamic design of the RainVUE™20 prevents wind from carrying the rainfall away from the collecting vessel. With traditional cylindrical rain gages, wind can reduce the rainfall catch by up to 20%. The RainVUE™20 also includes a microprocessor that corrects for rainfall intensity and outputs an SDI-12 signal.

## Specifications

Sensor Type	Tipping bucket with magnetic reed switch
Material	<ul style="list-style-type: none"><li>› 2 mm-thick powder-coated aluminum (for main collector body)</li><li>› LM6 marine-grade aluminum (for base)</li></ul>
Output	SDI-12 version 1.4
Rainfall Intensity	1500 mm/h (60 in./h)
Operating Temperature Range	1° to 70°C
Rainfall per Tip	0.254 mm (0.01 in.)
Current Drain	<ul style="list-style-type: none"><li>› 0.8 mA or 1 mA (active)</li><li>› 0.07 mA (quiescent)</li></ul>
Measurement Uncertainty	› ±1% (0 to 500 mm/h intensity of rainfall)

› *Note: Accuracy over the rain intensity range requires a mechanical calibration that is within 1% at a 1 in./h intensity. RainVUE™20 sensors are calibrated at the factory to meet this specification but should be verified prior to deployment.*

- › ±1° (tilt)
- › ±0.25°C (temperature)
- › ±0.5 V (supply voltage)

Orifice Diameter	20.0 cm (7.87 in.)
Height	43.5 to 46.5 cm (17.1 to 18.3 in.) with feet adjustment
Weight	6 kg (13 lb)

For comprehensive details, visit: [www.campbellsci.eu/rainvue20](http://www.campbellsci.eu/rainvue20) 



80 Hathern Road, Shepshed, LE12 9GX UK | +(0)1509 828888 | [sale@campbellsci.co.uk](mailto:sale@campbellsci.co.uk) | [www.campbellsci.eu](http://www.campbellsci.eu)  
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2022 Campbell Scientific, Ltd. | 04/10/2022