



Greatly Expands Control Capacity

Use multiple modules for up to 256 control ports

Overview

The SDM-CD16ACA allows a Campbell Scientific datalogger to automatically activate external ac or dc devices such as

motors, pumps, heaters, valves, and fans.

Benefits and Features

- ▶ Allows the data logger to automatically turn devices on or off when a threshold (for example, temperature or water depth) has been reached
- ▶ Includes LEDs that indicate when a port is active
- ▶ Provides a manual override for each port
- ▶ UL/CUL approved product
- ▶ Addresses up to 15 SDM-CD16 ACAs, allowing up to 240 ports to be controlled by one datalogger

Technical Description

The SDM-CD16ACA has a toggle switch that provides three positions: ON and OFF for manual override, and AUTO for data logger control.

- ▶ In the ON position, the common (COM) and normally open (NO) contacts are closed.
- ▶ In the OFF position, the normally open contact is open.
- ▶ In the AUTO position, the state of the relay is controlled by the SDM command issued through the data logger's control ports or SDM terminal.

SDM Operation

The SDM-CD16ACA is a synchronously addressed data logger peripheral. Data logger control ports 1, 2, and 3 are used to address the SDM-CD16ACA, then clock out the desired state of each of the 16 control ports. Up to 16 SDM-CD16ACAs may be addressed, making it possible to control a maximum of 256 ports from the first three data logger control ports.

Specifications

Function	Allows a data logger to automatically activate external ac or dc devices such as motors, pumps, heaters, valves, and fans.	Number of Channels	16
		Operating Temperature	-40° to +55°C
		Humidity	Non-condensing

Contact Operation	Single pole double throw (break before make)
Contact Material	Gold-clad silver
Coil Voltage	11 to 18 Vdc
Coil Resistance	360 Ω \pm 10%
Expected Life (contact closures)	Mechanical 10 ⁷
Actuation/Release Time	~4 ms
Toggle Switch	<ul style="list-style-type: none"> › ON/OFF manual override › AUTO for data logger control
Operating Voltage	12 Vdc nominal (11 to 18 Vdc)
Standards	Underwriters Laboratories (UL) listed product (E162021)

Dimensions 24.6 x 5.1 x 8.6 cm (9.7. x 2.0 x 3.4 in.)

Weight 0.8 kg (1.8 lb)

Individual Contact Ratings

Normally Open Rating

- › 5 A (@ 30 Vdc)
- › 5 A (@ 125 Vac)
- › 5 A (@ 250 Vac)

Normally Closed Rating

- › 1 A (@ 30 Vdc)
- › 3 A (@ 125 Vac)
- › 2 A (@ 250 Vac)

Current Drain @ 12 Vdc

Quiescent 6 mA

Per Active LED 45 mA (switch on or auto active)

For comprehensive details, visit: www.campbellsci.eu/sdm-cd16aca 



80 Hathern Road, Shepshed, LE12 9GX UK | +(0)1509 828888 | sale@campbellsci.co.uk | www.campbellsci.eu
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA