



Forecast Winter Treatments for Road Surfaces

Prevent traffic accidents and loss of life

Overview

The Wintersense SDI-12 is a remote road surface temperature sensor designed for use with your road weather information systems (RWIS). It is an easy-to-deploy, non-invasive, compact, and lightweight sensor that you can mount on existing roadside structures such as streetlight columns or RWIS towers. The Wintersense SDI-12 has a

cabled connection for power and communications with an RWIS station or data logger for data storage and forwarding.

With accurate, real-time road surface temperature data, you can forecast your winter road treatments, preventing traffic accidents and potential loss of life.

Benefits and Features

- › Accurate
- › Non-invasive
- › Easy to install
- › Simple to maintain
- › Compatible with most data loggers and RWIS
- › Remote firmware updates

Technical Description

The Wintersense SDI-12 is equipped with a thermopile sensor that detects the presence of thermal radiation emitted from the target surface. The sensor also has an integrated optical filter that cuts off the visible and near-infrared radiation flux so that you get optimum ambient and sunlight immunity. These features, combined with an eight-second signal-averaging algorithm, provide you with best-of-class data for these measurement parameters:

- › Road surface temperature
- › Air temperature
- › Relative humidity
- › Dewpoint
- › Installation angle
- › Sensor temperature

Specifications

Operating Temperature Range -40 to +70°C (-40 to +160°F)

Operating Humidity Range 0 to 100%

Internal Enclosure Sealing IP65 (minimum)

Typical Power Consumption > 14 mA (active)

Consumption @ 12 Vdc > 0.1 mA (idle)

Supply Voltage Range 5 to 18 Vdc

Field of View (FOV)	<i>Note: Use our field-of-view tool to make your calculations and install your Wintersense appropriately.</i>
Digital Output	SDI-12
Default SDI-12 Address	0
Response Time (to M!)	8 s to read all sensor outputs using SDI-12 commands
Sensor Warm-up Time	If power is switched, allow 3 s for warm-up before taking a measurement.
Dimensions	350 x 200 x 100 mm (13.8 x 7.9 x 4.0 in.)
Weight	1.4 kg (3 lb)

Road-Surface Temperature

Measurement Range	-40 to +70°C (-40 to +160°F)
Accuracy at -40 to +60°C	<ul style="list-style-type: none"> › ±1°C or better › <i>Note: Accuracy is temperature dependent. The quoted accuracy is against a blackbody source within the ambient temperature range of -20 to +50°C and object temperature range of -40 to +60°C.</i>

Resolution ±0.01°C

Air Temperature

Measurement Range	-40 to +70°C (-40 to +160°F)
Accuracy at -40° to +70°C	±0.2°C
Resolution	±0.01°C

Relative Humidity

Measurement Range	0 to 100%
Accuracy at -40 to +60°C	< ±3%
Resolution	0.1%

Dew Point Temperature (Calculated)

Measurement Range	-40 to +70°C (-40 to +160°F)
Accuracy at -35 to +50°C	<ul style="list-style-type: none"> › ±0.2°C › <i>Note: The calculated dew point temperature is found from Tetens' equation solved for dew point with coefficients optimized for the temperature range -35 to +50°C.</i>
Resolution	0.1°C

For comprehensive details, visit: www.campbellsci.eu/wintersense-sdi-12 



80 Hathern Road, Shepshed, LE12 9GX UK | +(0)1509 828888 | sale@campbellsci.co.uk | www.campbellsci.eu
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2022 Campbell Scientific, Ltd. | 12/13/2022