



## 8 km Ceiling Tactical LIDAR Ceilometer

DC-powered for quick tactical deployment for military or civilian use

### Aperçu

The SkyVue™8M Tactical LIDAR Ceilometer is ideal for quick tactical deployment (for permanent or temporary installation) for military or civilian applications in all climates.

The ceilometer's robust construction requires minimal maintenance and enables continuous use and multiple deployments in the harshest of environments. Designed to be easily portable, the SkyVue 8M has unique quick-deploy stabilizing legs, low weight, and a compact design with a beige finish and two canvas covers to suit all applications.

The SkyVue 8M has many standard features, including a tilting base, a two-axis inclinometer for automatic correction of cloud heights, heaters, blowers, and a sun filter for operation under all conditions—making deployments possible around the world.

The SkyVue 8M has an operating range of 8 km and meets or exceeds all the necessary ICAO, CAA, and WMO requirements and recommendations.

Unique standard features include an easy-to-operate stratocumulus calibration and twin clocks to augment its many continuous diagnostic self-checks and provide assurance of continuous, reliable, and accurate performance.

### Avantages et caractéristiques

- › Single-lens design for high signal-to-noise ratio and maximized detector sensitivity, resulting in greater performance at low and high altitudes
- › Low weight and small form factor for maximum portability
- › Quick-deploy stabilizing legs
- › Multiple camouflage options with shroud
- › Low power consumption with multiple power options
- › Unique continuous comparison of two separate internal quartz clocks to eliminate possibility of clock drift, ensuring measurement confidence
- › User-friendly stratocumulus calibration capability and easy test with provided calibrator plate for easy field setup and calibration

### Description technique

The SkyVue 8M LIDAR ceilometer measures cloud height and vertical visibility for aviation and meteorological applications. Using LIDAR (Light Detection And Ranging) technology, the ceilometer transmits fast, low-power laser pulses into the

atmosphere and detects backscattered returns from clouds and aerosols above the instrument.

A unique, efficient single-lens design increases optical signal-to-noise ratio and allows for larger optics in a compact package, improving accuracy and measurement performance.

This approach, along with state-of-the-art electronics, provides a powerful and stable platform from which to measure cloud height and vertical visibility to high accuracy.

The SkyVue 8M measures the atmosphere with high stability and repeatability, delivering excellent performance in even the harshest of conditions.

The SkyVue 8M provides information on cloud height, sky condition (up to five layers), vertical visibility, and raw backscatter profiles to a range of 8 km.

## Spécifications

Dimensions	763 x 360 x 253 mm (30.0 x 14.2 x 10.0 in.) including base and handle
------------	---

Weight	18 kg (39.7 lb) excluding cables
--------	----------------------------------

### Instrument Performance

Reporting Range	0 to 8 km (0 to 26,250 ft)
-----------------	----------------------------

Minimum Reporting Resolution	5 m (16.4 ft)
------------------------------	---------------

Hard Target Range Accuracy	±0.25%, ±4.6 m (15.1 ft)
----------------------------	--------------------------

Reporting Cycle	2 to 600s
-----------------	-----------

Cloud Layers Reported	Up to four layers (up to five layers in Sky Condition)
-----------------------	--

Sky Condition	Up to five layers with cover in oktas according to WMO requirements for SYNOP and METAR codes as standard
---------------	---

Laser Type	InGaAs
------------	--------

Laser Wavelength	912 nm (±5 nm)
------------------	----------------

Military Specification	<ul style="list-style-type: none"> <li>› DEF STAN 00-035 (for resistance to shock and vibration)</li> <li>› MIL-STD-80g (for resistance to shock and vibration)</li> </ul>
------------------------	--

### Electrical Specification

Power Source	<ul style="list-style-type: none"> <li>› 10 to 40 Vdc, current drain 9 A at 12 Vdc, 4.5 A at 24 Vdc</li> <li>› DC power source only</li> </ul>
--------------	--

Interfaces-Maintenance	USB 2.0 (USB 1.1 compatible)
------------------------	------------------------------

Interfaces-Baud Rate	300 to 115200 bps
----------------------	-------------------

Interfaces-Data	RS-232 / RS-422* / RS-485* / Ethernet option *The standard wiring of the military output connector does not support RS-422 and RS-485 functionality. Functionality to support RS-485 and RS-422 are available by special order only.
-----------------	--

### Environmental Specification

Temperature Range	-40° to +60°C (-40° to +140°F)
-------------------	--------------------------------

Humidity Range	0 to 100% RH
----------------	--------------

IP Rating	IP66 (NEMA 4X)
-----------	----------------

Maximum Wind Speed	55 m/s (123 mph) if securely attached to the ground (without camouflage covers)
--------------------	---

### Compliance and Testing

-NOTE-	<i>Further details regarding compliance and testing are available upon request.</i>
--------	---

EMC Compliance	EN 61326-1:2013
----------------	-----------------

Electrical Safety Compliance	EN 61010-1:2010
------------------------------	-----------------

Laser Safety Compliance	EN 60825-1:2014
-------------------------	-----------------

Eye Safety Standard	Class 1M
---------------------	----------

Vibration	BS EN 60068-2-6:2008 Test Fc: Vibration (Sinusoidal)
-----------	--

Frequency Range	5 to 150 Hz (exceeds Lloyd's Register test levels)
-----------------	--

Pour plus d'informations, visitez le site : [www.campbellsci.fr/skyvue8m](http://www.campbellsci.fr/skyvue8m) 