

## New York: Bridge Load Testing

*Strain gages monitor structural performance*



*Twin suspension cables on the north side of the Williamsburg Bridge point toward Manhattan. The traffic lanes below are cantilevered and outside the suspension, attributes that made the monitoring both vital and unique. (Photo courtesy of Dave Frieder, all rights reserved)*

Lehigh University researchers have been on the forefront of field instrumentation and testing of bridges, buildings and other structures for over 50 years. They have developed a vast database and considerable experience in the field testing and evaluation of highway and rail structures. Field testing and evaluation is a particularly challenging area of structural research. It is the only method to accurately evaluate the true behavior of a structure in real-time under actual loads. Field measurements are the link that connects and validates laboratory testing and computer modeling to the behavior of real structures.

It is well known that accurate interpretations of structural behavior require accurate data. However, it is clear that it is much more difficult to collect data several hundred feet in the air over a river, in the wind and cold, than it is in a laboratory. Aside from environmental obstacles, there are many variables that must be addressed prior to making an accurate interpretation of the measurements. Thus, a thorough understating of data acquisition systems, sensors and structural behavior is essential. Of utmost importance is a data acquisition system that can consistently perform under these adverse conditions. Lehigh University researchers have found the Campbell Scientific CR9000 Measurement and Control Systems to be extremely robust, and capable of withstanding the harshest field environments. They are the workhorses of our infrastructure monitoring program.

### Case Study Summary

#### Application

A monitoring project to investigate in-situ stress-ranges and better characterize the behavior of this complex structural system

#### Location

New York, New York, USA

#### Products Used

CR9000X, CR9000

#### Contributors

Rob Connor, ATLSS Lehigh University

#### Participating Organizations

City of New York

#### Measured Parameters

Strain, vibration

An example of a recently completed field testing project involves on-site measurements and long-term remote monitoring of the Williamsburg Bridge in New York City, NY, which is currently undergoing a major rehabilitation. A significant portion of this project involves the replacement of the existing concrete-filled grid deck on both the south and north inner and outer roadways with a steel orthotropic deck. Along with a comprehensive laboratory testing program, an in-depth field instrumentation and testing program was also conducted on the south outer roadway. This study was performed to investigate in-situ stress-ranges and better characterize the behavior of this complex structural system and its relationship to the laboratory response. Data were collected using a CR9000. During controlled load tests, data were collected from 82 strain gages at sampling rates as high as 200 Hz. All data were temporarily stored on PCMCIA cards installed in the datalogger. These data were subsequently copied to the laptop at the end of each test for processing and back-up. The compact and rugged CR9000 performed superbly throughout the testing program. The ability to observe and review data in real-time was invaluable during the testing.

A second portion of the program consisted of nearly seven months of remote monitoring. Data were collected using the CR9000 system described above. Program upload and data download were achieved with two modems specially configured by Lehigh University's Advanced Technology for Large Structural Systems (ATLSS) researchers. One modem was placed at the site, the other in an office at the ATLSS laboratory. The data were downloaded to a desktop PC every one to 14 days. The entire data acquisition system was stored in a steel box that was bolted to the west face of floorbeam 64E.

Access to the structure was very difficult. The constant traffic and remote location of the logger posed a special problem to the monitoring program. Convenient, regular access was simply not possible. The CR9000 permitted Lehigh researchers to collect a considerable amount of data remotely, eliminating repeated trips to the bridge itself.

To minimize the volume of data collected, time histories were not recorded continuously. Rather, the CR9000 was programmed to begin recording when the stresses induced by live loads exceeded predetermined triggers. The appropriate magnitude of the triggers was determined *a priori* from the controlled load tests.

For example, assume it was determined that heavy trucks observed to produce a peak stress of 6.0 ksi at a given location. Software triggers were then set at 5.9 ksi for these gages. If the stress exceeded that value, the time history was recorded. Data were also recorded prior to the trigger event for a specified amount of time, say five seconds (i.e., a five-second buffer was maintained). The CR9000 continued to record for an additional specified time period, again, say five seconds and then stopped recording. These channels monitored as triggered time

histories were automatically re-zeroed on the whole and half hour using a digital balance algorithm. The appropriate length for the buffer and total recording time were determined on site. This technique provided sufficient time-dependent data and a method of verification for high stress range events to ensure that spurious signals were excluded from the stress range histograms.

Stress-range histograms were developed using the rainflow cycle counting method contained in the CR9000's instruction set. The stress-range histograms were generated continuously and did not operate on triggers, thus all cycles were counted. In addition, the histogram was updated every 10 minutes. Thus, in the event of a power failure, a minimal amount of data were lost. The stressrange bins were divided into 0.5 ksi intervals. The results of the research will be incorporated in the AASHTO LRFD Bridge Design Specifications.

View online at: [www.campbellsci.com/new-york-bridge-load-testing](http://www.campbellsci.com/new-york-bridge-load-testing) 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | [www.campbellsci.com](http://www.campbellsci.com)  
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2020 Campbell Scientific, Inc. | 03/30/2020