











Crossarms and Crossarm Brackets

Rugged attachment points



Crossarms are used with crossarm brackets to provide a rugged attachment point for securing meteorological sensors, antennas, and other peripherals to tripods and towers. The crossarms are designed to place sensors horizontally a few feet away from the midline of towers or tripods, thereby reducing the effects of the mounts on sensor measurements.

		<i>Crossarm Material</i>	<i>Mounting Material</i>	<i>Pipe Outer Diameter</i>	<i>Pipe Length</i>
<p>CM204 4 ft Crossarm with One CM210 Mounting Kit</p> <p>Popular</p> 		1 in. IPS anodized aluminum pipe	304 stainless-steel bracket with stainless-steel U-bolts and hardware	3.34 cm (1.315 in.)	1.2 m (4 ft)
<p>CM202 2 ft Crossarm with One CM210 Mounting Kit</p> <p>Popular</p> 		1 in. IPS anodized aluminum pipe	304 stainless-steel bracket with stainless-steel U-bolts and hardware	3.34 cm (1.315 in.)	0.6 m (2 ft)
<p>CMB200 Crossarm Brace Kit</p> <p>Popular</p> 		304 stainless steel	304 stainless-steel pipe with 304 stainless-steel brackets	2.54 cm (1.0 in.)	0.86 m (2.83 ft)
<p>CM203 3 ft Crossarm with One CM210 Mounting Kit</p> 		1 in. IPS anodized aluminum pipe	304 stainless-steel bracket with stainless-steel U-bolts and hardware	3.34 cm (1.315 in.)	0.9 m (3 ft)

		<i>Crossarm Material</i>	<i>Mounting Material</i>	<i>Pipe Outer Diameter</i>	<i>Pipe Length</i>
CM206 6 ft Crossarm with One CM210 Mounting Kit 		1 in. IPS anodized aluminum pipe	304 stainless-steel bracket with stainless-steel U-bolts and hardware	3.34 cm (1.315 in.)	1.8 m (6 ft)
CM204SS 4 ft Stainless-Steel Crossarm with One CM210 Mounting Kit 		Stainless-steel pipe	304 stainless-steel bracket with stainless-steel U-bolts and hardware	3.175 cm (1.25 in.)	1.2 m (4 ft)
CM202SS 2 ft Stainless-Steel Crossarm with One CM210 Mounting Kit 		Stainless-steel pipe	304 stainless-steel bracket with stainless-steel U-bolts and hardware	3.175 cm (1.25 in.)	0.6 m (2 ft)
CM210 Crossarm-to-Pole Mounting Kit 		—	304 stainless-steel bracket with stainless-steel U-bolts and hardware	—	—

For comprehensive details, visit: www.campbellsci.com/crossarms-crossarm-brackets 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA