



Multiply Capability

Provides excitation current for up to 8 model 229 soil-water sensors

Overview

The CE8 is a current-excitation module that applies a constant current to the heating element of up to eight 229 Heat Dissipation Water Matric Potential Sensors. A current-excitation

module is required when you use 229 sensors to measure soil water matric potential.

Benefits and Features

- › Provides excitation current for up to eight 229 sensors
- › Allows up to eight AM16/32-series multiplexers to be connected, which significantly expands the system's capacity
- › Compatible with most Campbell Scientific data loggers

Detailed Description

A CE8 current excitation module can provide a constant current to the heating element of the 229. The CE8 sources current for up to eight 229s. The module requires a 12 Vdc power source. The number of 229 sensors measured by one data logger can be increased by connecting a CE8 to one or more AM16/32-series multiplexers. Up to eight multiplexers can be connected to the CE8.

Note: The CE8 module switches currents that are greater than 30 mA, which degrades the contact surfaces of the mechanical relays. Therefore, the multiplexer channels to which the CE8 have been connected may become unsuitable for other applications. (Refer to the multiplexer manual for more information.)

Specifications

Output	50 mA ±0.25 mA (regulated)
Output Channels	8
Power	12 Vdc source required

Active Current Drain	25 mA + (50 mA) x (number of 229s connected to the CE8)
Compliance	CE compliant

Dimensions

16.5 x 5.4 x 2.7 cm (6.5 x 2.1 x 1.1
in.)

Weight

184 g (6.5 oz)

For comprehensive details, visit: www.campbellsci.com/ce8 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | [USA](#)

© 2019 Campbell Scientific, Inc. | 08/16/2019