



Simple to Use, Easy to Maintain

Low-power option for use in
Australia

Overview

By using Campbell Scientific's external line of cellular modules, system integrators, OEMs, and large end users can avoid costly, time-consuming maintenance visits to remote devices around the world.

The CELL200 series of external cellular modules are 4G LTE cellular devices that provide serial or CS I/O connectivity to a number of cellular networks, including Verizon, AT&T, T-Mobile USA, Rogers, Bell, Telstra, and Telus. The networking and carrier used by the CELL200 series is determined by the model used and the SIM card inserted into the device.

The CELL220 has very low power consumption when compared to other cellular modems: 14 mA at idle, 39 mA when active, and 200 μ A when in low power mode.

When coupled with Campbell Scientific data services, these devices are ready for you to use out of the box. There is no

need for you to work with cellular carriers for provisioning and experience the accompanying hassle.

The CELL220 is part of the CELL200 series of modems that includes:

- › CELL205 for use with AT&T
- › CELL210 for use with Verizon
- › CELL215 for use in EMEA countries
- › CELL220 for use in Australia
- › CELL225 for use in Japan

Note: The CELL220 does not ship with a SIM card unless the cellular modem was provisioned with/for Campbell Scientific cellular data services; the SIM card is provided by the carrier when signing up for service. For more information, visit the [Cellular Data Services page](#).

Benefits and Features

- › Includes everything needed for use with a Campbell Scientific data logger or smart sensor
- › Low power consumption for solar-powered sites
- › Easy integration, setup, and installation
- › No moving parts and low maintenance
- › Compatible with modern Campbell Scientific data loggers
- › Compatible with Edlog-era data loggers in serial server mode
- › 4G LTE networking
- › Ready for out-of-the-box use with Campbell Scientific data services



Specifications

Host Interface	<ul style="list-style-type: none">› CS I/O communications port, DB9 male› RS-232 serial port, DB9 female› USB version 2.0 with micro-B connector
RF Connectors	2 SMA antenna connectors (primary and diversity)
Operating Temperature Range	-40° to +80°C
SIM Interface	3FF
Dimensions	13.46 x 8.1 x 2.86 cm (5.3 x 3.19 x 1.13 in.)
Weight	215.5 g (7.6 oz)

Cellular WAN

Network Technology	4G (with automatic fallback to 3G)
--------------------	------------------------------------

Carrier Approval	Telstra
LTE	2100(B1), 1800(B3), 850(B5), 2600(B7), 700(B28)
WCDMA	1900(B1), 850(B5)

Data Speeds

LTE	<ul style="list-style-type: none">› Max 10 Mbps (download)› Max 5 Mbps (upload)
WCDMA	<ul style="list-style-type: none">› Max 384 Kbps (upload)› Max 384 Kbps (download)
GSM EDGE	<ul style="list-style-type: none">› Max 296 Kbps (download)› Max 236.8 Kbps (upload)
GSM GPRS	<ul style="list-style-type: none">› Max 85.6 Kbps (upload)› Max 107 Kbps (download)

For comprehensive details, visit: www.campbellsci.com/cell220 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | [USA](#)

© 2019 Campbell Scientific, Inc. | 05/24/2019