



GRANITE 9

Measurement and Control Data-Acquisition System



Meeting Your Top Testing Priorities

Flexible for use in the lab and out in the field

Overview

The GRANITE™9 and GRANITE™10 are the most computationally powerful data-acquisition devices from Campbell Scientific. As an all-digital measurement and control DAQ, the GRANITE 9 is designed as the core of the data-

acquisition network, integrating with all GRANITE measurement modules, including the VOLT 108, VOLT 116, TEMP 120, VWIRE 305, and CH400.

Benefits and Features

- ▶ Traditional network connections via Ethernet port
- ▶ EPI port switch for high-speed connection to all GRANITE™ measurement modules
- ▶ Onboard storage of streaming data with 2 GB of DDR3 SDRAM and a 64 GB solid-state hard drive (SSD)
- ▶ Built-in GPS for network synchronization

Detailed Description

The GRANITE 9 enables you to perform the following:

- ▶ Standard measurement functions
- ▶ Advanced math and processing functions
- ▶ Control functions

A complete GRANITE system installation may include the following components:

- ▶ GRANITE Chassis
- ▶ GRANITE 9
- ▶ CH400
- ▶ Power source (mains or solar)
- ▶ Software

Specifications

-NOTE-

Additional specifications are listed

in the [GRANITE 9 Specifications](#).

Power Requirements	9.6 to 32 Vdc (voltage input)
Real-Time Clock Accuracy	±3 min. per year
Operating Temperature Range	<ul style="list-style-type: none"> › <i>Non-condensing environment</i> › -55° to +85°C (extended) › -40° to +70°C (standard)
Case Material	Stainless steel 304 and aluminum 6061
Communications Ports	<ul style="list-style-type: none"> › EPI › Ethernet › USB Micro B › USB host › CS I/O › 0 to 5 V serial › SDI-12 › RS-485 › RS-422 › CPI/RS-232
Data Storage Ports	<ul style="list-style-type: none"> › microSD › USB host
Digital I/O	8 terminals (C1 to C8) configurable for digital input and output. Terminals are configurable in pairs for 5 V or 3.3 V logic for some functions.
Internet Protocols	Ethernet, PPP, RNDIS, ICMP/Ping, Auto-IP (APIPA), IPv4, IPv6, UDP, TCP, TLS (v1.2), DNS, DHCP, SLAAC, Telnet, HTTP(S), SFTP, FTP(S), POP3/

	TLS, NTP, SMTP/TLS, SNMPv3, CS I/O IP
Communication Protocols	CPI, EPI PakBus, PakBus Encryption, SDM, SDI-12, Modbus RTU / ASCII / TCP, DNP3, custom user definable over serial, UDP, NTCIP, NMEA 0183, I2C, SPI
Warranty	<ul style="list-style-type: none"> › 3 years standard (against defects in materials and workmanship) › Optional: An additional 2 years (against defects in materials and workmanship), bringing the total to 5 years
Battery-backed SRAM for CPU Usage & Final Storage	4 MB
Data Storage	4 MB SRAM + 128 MB NOR flash (Storage expansion of up to 16 GB with removable microSD flash memory card.)
Active Current Drain, Average	<ul style="list-style-type: none"> › 495 mA input (12 V input) › 255 mA input (24 V input) › ~6 W
Static Vibrating-Wire Measurements	Not supported
Dimensions	21.4 x 12.0 x 5.0 cm (8.4 x 4.7 x 2.0 in.) Additional clearance required for cables and leads.
Weight	1.0 kg (2.2 lb)

For comprehensive details, visit: www.campbellsci.com/granite9 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA