



Measure Rapid Fluctuations in Atmospheric Water Vapor

Overview

The KH20 is a highly sensitive hygrometer designed for measurement of rapid fluctuations in atmospheric water vapor,

not absolute concentrations. It is typically used together with a CSAT3B in eddy-covariance systems.

Benefits and Features

- › Compatible with most Campbell Scientific data loggers
- › High frequency response suitable for eddy-covariance applications
- › Well-suited for long-term, unattended applications

Detailed Description

The KH20 is typically used with a CSAT3B Sonic Anemometer in eddy-covariance systems for measuring water vapor flux. This highly sensitive hygrometer measures rapid fluctuations in atmospheric water vapor. It does not measure absolute

concentrations. The KH20 is compatible with most of our data loggers.

Routine maintenance is required to keep source windows free of scale. The KH20 can be used with the window scaled if scaled calibration is used.

Specifications

Calibrated Range	1.7 to 19.5 g/m ³ (nominal)
Type	Ultraviolet krypton hygrometer
Input Voltage Range	10 V to 16 Vdc
Current Consumption	20 mA max (at 12 Vdc)
Power Consumption	0.24 W

Output Signal Range	0 to 5 Vdc
Cable Length	7.62 m (25 ft)
Mounting Pipe Length	50 cm (20 in.)
Dimensions	› 29 x 23 x 3 cm (11.5 x 9 x 1.25 in.) for sensor head



- › 64 x 38 x 18 cm (25 x 15 x 7 in.) for carrying case
- › 29 x 18 x 6.5 cm (11.5 x 7 x 2.5 in.) for rain shield with mount

- › 19 x 13 x 5 cm (7.5 x 5 x 2 in.) for electronics box

Weight

6.8 kg (15 lb)

For comprehensive details, visit: www.campbellsci.com/kh20 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | [USA](#)

© 2019 Campbell Scientific, Inc. | 08/16/2019