

Compact Weather Sensor for Wind with Compass



Measures Wind Speed and Direction

IEC 61724-1 Compliant

Overview

The MetSens200 compact weather sensor measures wind speed and direction via an ultrasonic sensor. An integrated electronic compass allows the MetSens200 to provide accurate, relative wind direction measurements without being oriented in a particular way, making installation easier. WMO average wind speed and direction and gust data are provided. The MetSens200 is compatible and easily integrated with the MeteoPV Solar Resource Platform and any Campbell Scientific data logger using SDI-12, RS-485, ModbusRS-485, or NMEA RS-232.

Benefits and Features

- Quality measurements
- Fast and simple to install

- Compact, integrated design
- Lightweight and robust

Specifications

Measurements Made	Wind direction and wind speed.
Sampling Rate	1 Hz
Digital Communication Modes	Serial RS-232, RS-485, SDI-12, NMEA, Modbus, ASCII
IP Rating	66
Compliance	 CE, RoHS Where applicable, all individual parameters meet or exceed specifications of IEC 61724-1 (2017, 2021).
Operating Temperature Range	-40° to +70°C
Operating Voltage	5 to 30 Vdc

Typical Current Drain @ 12 Vdc	 0.7 mA (eco-power mode; 1 hour polled) 25 mA (continuous high mode) 	
Weight	0.5 kg (1.1 lb)	
Wind Speed Measurement		

while speed measurement	
Measurement Range	0.01 to 60 m s ⁻¹
Accuracy	 ±3% (up to 40 m s⁻¹) ±5% (up to 60 m s⁻¹)
Resolution	0.01 m s ⁻¹
Starting Threshold	0.01 m s ⁻¹

Wind Direction Measurement		
Measurement Range	0° to 359°	
Accuracy	\pm 3° (up to 60 m s ⁻¹)	
Resolution	1°	

Compass	
Measurement Range	0 to 359°
Resolution	1°
Units of Measure	Degrees
Accuracy	±3°

For comprehensive details, visit: www.campbellsci.com/metsens200



 CAMPBELL
 Campbell Scientific, Inc.
 815 W 1800 N
 Logan, UT 84321-1784
 (435) 227-9120
 www.campbellsci.com

 SCIENTIFIC
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA