



PS150

12 V Power Supply with Charging Regulator and 7 Ah Sealed Rechargeable Battery



ETL Listed Class 2 Power Supply

Overview

The PS150 is a 12 Vdc power supply that includes a rechargeable 7 Ah valve-regulated lead-acid (VRLA) battery and charging regulator. Charging power for the PS150 is typically supplied by an unregulated solar panel, AC/AC transformer, or AC/DC converter. The PS150 provides charging with temperature compensation for optimal charging and battery

life. A maximum power point tracking algorithm is incorporated for solar inputs to maximize available solar charging resources.

The PS150 is ETL certified. The [ETL Mark](#) is proof of product compliance to North American safety standards.

Benefits and Features

- › Protects against high-amperage and high-voltage damage to power supply
- › Battery reversal protection
- › Allows simultaneous connection of two charging sources (e.g., solar panel, ac wall charger)
- › ETL listed Class 2 power supply

Detailed Description

The PS150 is a micro-controller-based smart charger with temperature compensation that optimizes battery charging and increases the battery's life. Two input terminals enable simultaneous connection of two charging sources. They also incorporate a maximum power point tracking algorithm for solar inputs that maximizes available solar charging resources.

The PS150 has several safety features intended to protect the charging source, battery, charger, and load devices. Battery-reversal protection is included, as well as ESD and surge protection on all of the PS150 inputs and outputs.

The PS150 replaced the PS100.

Specifications

Operational Temperature -40° to +60°C (VRLA battery manufacturers state that "heat kills

batteries" and recommend operating batteries at ≤ 50°C.)

Dimensions 19.3 x 7.6 x 10.6 cm (7.5 x 3 x 4.2 in.)

CHARGE - CHARGE Terminals (AC or DC Source)

AC 18 to 24 VRMS (internally limited to 1.2 Amps RMS)

DC 16 to 40 Vdc (internally limited to 0.85 Adc)

SOLAR Terminals (Solar Panel or Other DC Source)

-NOTE- Battery voltages below 8.7 V may result in < 3.0 A current limit because of fold-back current limit.

Input Voltage Range 15 to 40 Vdc

Maximum Charging Current 4.0 Adc typical (3.2 to 4.9 Adc depending upon individual charger)

Quiescent Current

No Charge Source Present 160 μ A at 13.7 Vdc

No Battery Connected 930 μ A at 30 V input voltage (ac or dc)

Battery Charging

-NOTE- The "T" represents temperature in degrees Celsius.

FLOAT Charging $V_{batt}(T) = 13.65 \text{ V} - (24 \text{ mV}) \times (T - 25) + (0.24 \text{ mV}) \times (T - 25)^2$

Accuracy $\pm 1\%$ (on charging voltage over -40° to $+60^\circ\text{C}$)

Power Out (+12 Terminals)

Voltage Unregulated 12 V from battery (4.65 A solid-state circuit breaker)

Standards ETL Listed Class 2 power supply

For comprehensive details, visit: www.campbellsci.com/ps150 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2023 Campbell Scientific, Inc. | 07/25/2023