



PVS5120D

Discrete Portable Automatic Liquid Sampler



Sampler Optimized for Data Logger or RTU Control

Vacuum technology for better samples

Overview

The PVS5120D is a discrete sampler that deposits its water samples into 1 to 24 containers. This sampler uses a vacuum sampler controller, the VSC100, to allow a Modbus RTU client, SDI-12 client device, simple pulse input, or Campbell Scientific PakBus data logger to control and communicate with the water sampler.

This sampler is lightweight, portable, and battery-powered. It can fit in a small-sized manhole and be suspended by a stainless-steel harness for sewer applications.

The PVS5120D can be used with a standard or large pump. The standard pump takes samples at 1.6 m/s (5.1 ft/s) for horizontal draws of 7.6 m (25 ft). The large pump takes samples at 2.2 m/s (7.1 ft/s) at 7.6 m (25 ft). Both of these velocities are typical values measured at sea level. Intake velocities will decrease as altitude increases.

Benefits and Features

- › Diagnostic feedback provided to the client device: bottle number, sample number, response code/message, sampler battery voltage
- › The installation of a bottle position encoder enables verification of arm position before sampling and then moving the arm if it is not centered above the correct bottle
- › Multiple bottle configurations possible: 1, 2, 3, 4, 6, 8, 12, 24
- › Auto deploy that automatically sets the purge and vacuum times based on hose length
- › Repeatable volume collection via metering chamber
- › Selectable internal or external power via three-way power switch
- › One control cable for all control types
- › An optional water present sensor detects the presence of water at the mouth of the sampler intake hose to ensure a sample is available

Detailed Description

The PVS5120D uses an external vacuum pump to draw water through intake tubing, instead of the traditional peristaltic pump that induces flow by squeezing flexible tubing. Because

the vacuum method disturbs the water samples less, they better represent the original water solution, especially if the

solution has high concentrations of suspended solids.

To prevent cross contamination, the sampler uses air pressure (up to 28 psi) to purge the tubing of excess water. The

standard pump can lift as high as the large pump and is appropriate for most applications—especially when the power budget is a concern. The large pump is appropriate for applications with long hose distances or high lifts because it provides higher pumping velocity.

Specifications

| | |
|-------------------------------|--|
| Specialized Applications | Fits in small-sized manholes. Can be suspended by stainless-steel harness for sewer applications. |
| 5/8 Inch ID Tubing Compatible | No |
| Sample Container | twenty-four 0.5 L bottles or twenty-four 1 L bottles |
| Enclosure | LLDPE (linear low-density polyethylene), three-piece construction, and stainless-steel fittings |
| Cooling System | Insulated container wall, cavity space for ice |
| Horizontal Velocity | Refer to the " PVS5120 Intake Velocity versus Hose Length at Sea Level " plot. |
| Storage Temperature Range | -20° to +50°C |
| Operating Temperature Range | <ul style="list-style-type: none"> › 0 to 40°C (large pump) › 0 to 50°C (standard pump) |
| Operating Voltage | <ul style="list-style-type: none"> › 12 Vdc (nominal) › 16 Vdc (maximum) › 10.8 Vdc (minimum) |
| Body Case Diameter | 42.8 cm (16.85 in.) |
| Height | <ul style="list-style-type: none"> › 80.9 cm (31.875 in.) › 96.2 cm (37.875 in.) with extended base |

Weight

| | |
|---|-----------------|
| Sampler with Standard Pump and No Battery | 10.4 kg (23 lb) |
| Sampler with Large Pump and No Battery | 11.8 kg (26 lb) |
| 7 Ah Battery | 1.8 kg (4 lb) |
| 17 Ah Battery | 6.3 kg (14 lb) |

Controller

| | |
|----------------------------|---|
| Sampler Triggering Methods | <ul style="list-style-type: none"> › SDI-12 Client Device › Modbus RTU Client › Campbell Scientific PakBus data logger › Pulse trigger (1 to 10,000 pulses) |
|----------------------------|---|

| | |
|-------------------------|---|
| | › Time-based sampling (stand alone) |
| RS-485 Communication | Can return sampler status when triggering samples via pulse or time-based control. |
| Backup Power Source | Internal lithium battery maintains program settings and information in case of power failure. |
| Bottle Position Encoder | Verifies arm position and moves to correct bottle if it is out of position. |
| Multi-purpose Button | Service sampler, collect manual sample, and auto deploy |
| Auto Deploy | Automatically sets the purge and vacuum times based on hose length (between 25 and 100 ft) |
| Sampler Status/Feedback | Bottle number, sample number, response code, sampler battery voltage (available after every sample) |

Vacuum System

| | |
|---------------------------------------|---|
| Pinch Valve | Fixed – normally open |
| Purge Cycle | Adjustable from 1 to 800 s (280 s for SDI-12) |
| Suction Cycle | Variable (until liquid contacts level electrode in metering chamber or adjusts automatically to two times the purge time) |
| Horizontal Maximum Transport Distance | 67 m (220 ft) |

Vacuum System

| | |
|----------------------------------|--|
| Metering Chamber Cover | <ul style="list-style-type: none"> › Nylon (standard) › Teflon (option) |
| Volume Control Tube | 316 stainless steel |
| Metering Chamber Level Electrode | 316 stainless steel |
| Intake Hose | Ordered as a common accessory. Campbell Scientific offers PVC hose with 25-ft and user-specified lengths. Intake end can have a lead sinker or stainless-steel |

strainer. Sampler end can have a clamp or quick-connect termination.

Discharge Hose Material

- › Latex (standard)
- › Options include Teflon lined, silicon.

For comprehensive details, visit: www.campbellsci.com/pvs5120d 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | INDIA | SOUTH AFRICA | SPAIN | THAILAND | UK | USA

© 2022 Campbell Scientific, Inc. | 04/10/2022