

SkyVue⁸

LIDAR Ceilometer

8 km Ceiling LIDAR Ceilometer

Cloud measurement with state-of-the-art signal processing



Overview

The SkyVueTM8 LIDAR Ceilometer is ideal for measuring cloud base heights and vertical visibility at airports, helipads (onshore or offshore), and other meteorological applications. The SkyVue 8 measures the atmosphere with high stability and repeatability, providing you with information on cloud base heights, sky condition (up to five layers), vertical visibility, and raw backscatter profiles. Notably, the ceilometer meets or exceeds all the necessary International Civil Aviation Organization (ICAO), Civil Aviation Authority (CAA), and World Meteorological Organization (WMO) requirements and recommendations.

Because of its robust construction, the SkyVue 8 only requires minimal maintenance and can be continuously used in either static or mobile applications in harsh environments. Its compact design and low weight of 18 kg make it easy to transport and deploy.

With an operational reporting range of 8 km, the SkyVue 8 has one of the highest in its class. It is easy to use yet features advanced signal processing and unique optics to provide superior resolution and performance.

The SkyVue 8 has many standard features—from a tilting base and two-axis inclinometer for automatic correction of cloud base heights to heaters, blowers, and a sun filter for operation under all conditions—making deployments possible around the world.

Unique standard features include an easy-to-operate stratocumulus calibration, long-life back-up battery, and twin clocks to augment its many continuous diagnostic self-checks and provide assurance of continuous, reliable, and accurate performance.

Learn more about our [CampbellAeroTM Automated Weather Observing System \(AWOS\) Solution](#) and our [CampbellAero Software](#).

Benefits and Features

- Single-lens design for high signal-to-noise ratio and maximized detector sensitivity, resulting in greater performance at low and high altitudes
- High performance and high specification at a competitive price
- Low power consumption
- Tilt angles to 24 degrees, improving performance during precipitation events and reducing impact of solar glare
- Unique continuous comparison of two separate internal quartz clocks to eliminate possibility of clock drift and ensure measurement confidence
- User-friendly stratocumulus calibration capability and easy test with a calibrator plate provided as standard for easy field calibration



Detailed Description

The SkyVue 8 LIDAR ceilometer measures cloud base heights and vertical visibility for meteorological and aviation applications. Using LIDAR (Light Detection And Ranging) technology, the ceilometer transmits fast, low-power laser pulses (not harmful to eyes) into the atmosphere and detects backscattered returns from clouds and aerosols above the instrument.

A unique, efficient, single-lens design increases optical signal-to-noise ratio and allows for larger optics in a compact package, improving accuracy and measurement performance.

This approach, along with state-of-the-art electronics, provides a powerful and stable platform from which to measure cloud base heights and vertical visibility to high accuracy. The SkyVue 8 measures the atmosphere with high stability and repeatability, delivering excellent performance in even the harshest of conditions.

The SkyVue 8 provides information on cloud base heights, sky condition (up to five layers), vertical visibility, and raw backscatter profiles to a range of 8 km.

The unique stratocumulus calibration capability, which allows users to calibrate measurements of scatter coefficients, uses a simple and user-friendly field method, giving complete confidence in the scatter profiles reported and removes the requirement to have the unit sent back for calibration.

Reliable range measurement is further assured by cross-checking two separate internal quartz clocks, eliminating the possibility of unidentified errors due to clock drift.

The SkyVue 8 can be tilted at various angles up to 24 degrees. Tilting the SkyVue 8 by even a few degrees can be important, as it allows the ceilometer to resist high levels of reflection from large raindrops and frozen particles that can impair vertical-type sensors. The tilt also improves rain run-off on the ceilometer window, resulting in a much higher performance compared with vertical ceilometers.

Tilting to 24 degrees also means that it can be operated anywhere in the world without the sun shining into the lens and resulting in missing data. An internal two-axis inclinometer provides automatic correction of cloud base heights at all angles, ensuring ease of installation and confidence that cloud base heights are automatically corrected throughout the lifetime of the installation.

The SkyVue 8 complies with ICAO, CAA, and WMO guidance and meets or exceeds all recommendations and specifications. (This includes ICAO 9837, ICAO Annex 3, CAP 437, and CAP 746.)

Specifications

Dimensions	737 x 294 x 240 mm (29.0 x 11.6 x 9.5 in.) including tilt base
Power Supply Cable Length	10.06 m (33 ft)
Data Cable Length	10.06 m (33 ft)
Weight	18 kg (39.7 lb)

Instrument Performance

Reporting Range	0 to 8 km (0 to 26,250 ft)
Minimum Reporting Resolution	5 m (16.4 ft)

Hard Target Range Accuracy	±0.25%, ±4.6 m (15.1 ft)
Reporting Cycle	2 to 600 s
Cloud Layers Reported	Up to four layers
Sky Condition	Up to five layers with cover in oktas according to WMO requirements for SYNOP and METAR codes as standard
Vertical Visibility	Reported when there is obscuration but no clouds detected
Laser Type	InGaAs
Laser Wavelength	912 nm (±5 nm)

Specifications

Electrical Specification

Power Source	<ul style="list-style-type: none">■ AC power source■ 115/230 Vac $\pm 15\%$ (auto switching), 50 to 60 Hz
	Power drain from 230 V is 15 W minimum, up to 380 W with all the heaters on. (Optional current limited mode: 250 W max.)

Battery	Internal 12 V 7 Ah battery backup
---------	-----------------------------------

Interfaces	■ Data - RS-232/RS-422/RS-485/Ethernet option
	■ Maintenance - USB 2.0 (USB 1.1 compatible)
	■ Baud Rate - 300 to 115,200 bps

Environmental Specification

Temperature Range	■ -40° to $+60^{\circ}\text{C}$ (-40° to $+140^{\circ}\text{F}$) excluding battery
	■ -50° to $+60^{\circ}\text{C}$ (-58° to $+140^{\circ}\text{F}$) This extended version is available as a special. Contact Campbell Scientific for more information.

Humidity Range	0 to 100% RH
----------------	--------------

IP Rating	IP66 (NEMA 4X)
-----------	----------------

Maximum Wind Speed	55 m/s (123 mph)
--------------------	------------------

Compliance and Testing

-NOTE-	<i>Further details regarding compliance and testing are available upon request.</i>
---------------	---

EMC Compliance	EN 61326-1:2013
----------------	-----------------

Electrical Safety Compliance	EN 61010-1:2010
------------------------------	-----------------

Laser Safety Compliance	EN 60825-1:2014
-------------------------	-----------------

Eye Safety Standard	Class 1M
---------------------	----------

Vibration	BS EN 60068-2-6:2008 Test Fc: Vibration (Sinusoidal)
-----------	--

Frequency Range	5 to 150 Hz (exceeds Lloyd's Register test levels)
-----------------	--

