



## SP230SS Heated Pyranometer



## All-Season Pyranometer

Heater prevents snow, frost, and dew accumulation

### Overview

The SP230SS pyranometer, manufactured by Apogee, includes a 0.18 W internal heater and an elevated base that allow it to provide solar radiation measurements during the most severe weather. Its small heater draws just 15 mA of current, allowing it to be powered by a small solar panel and battery—even on

days with a short duration of daylight and at high latitudes (far away from the equator).

This pyranometer features an IP67-rated, marine-grade 316L connector that allows the user to easily swap sensors for recalibration or to replace damaged cables.

### Benefits and Features

- › Designed to prevent snow, frost, and dew accumulation
- › Heater uses 1/80<sup>th</sup> of the power that other heated pyranometers use, making it ideal for remote battery-powered applications
- › Measurement waveband of 360 to 1120 nm
- › Compatible with most Campbell Scientific data loggers
- › Dome-shaped head prevents water from accumulating on the sensor head

### Detailed Description

The SP230SS uses a silicon photovoltaic detector mounted in a cosine-corrected head to provide solar radiation measurements. It is calibrated against a Kipp & Zonen CM21 thermopile pyranometer to accurately measure sun plus sky radiation for the spectral range of 360 to 1120 nm. The

SP230SS outputs a millivolt signal that Campbell Scientific data loggers can measure.

**Note:** Sensors calibrated to the 360 to 1120 nm spectral range should not be used under vegetation or artificial lights.

### Specifications

Light Spectrum Waveband	360 to 1120 nm (wavelengths where response is 10% of maximum)
-------------------------	---

Measurement Range	0 to 1750 W/m <sup>2</sup> (full sunlight ≈1000 W/m <sup>2</sup> )
Heater	780 Ω, 15.4 mA current drain, 185 mW power at 12 Vdc
Absolute Accuracy	±5% for daily total radiation
Sensitivity	(0.2 mV/W/m <sup>2</sup> )
Calibration Factor	5 W/m <sup>2</sup> /mV
Cosine Response	±5% at 75° zenith angle; ±1% at 45° zenith angle

Temperature Response	-0.04 ±0.04% per °C
Long-Term Stability	< 2% per year
Operating Temperature Range	-40° to +70°C
Relative Humidity Range	0 to 100%
Diameter	3.15 cm (1.24 in.)
Height	12.75 cm (5.02 in.)
Weight	142.0 g (5.01 oz) with 2 m (6.56 ft) cable

For comprehensive details, visit: [www.campbellsci.com/sp230ss](http://www.campbellsci.com/sp230ss) 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | [www.campbellsci.com](http://www.campbellsci.com)  
 AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | [USA](#)

© 2019 Campbell Scientific, Inc. | 03/28/2019