



Sturdy, Long-Term Instrument Mount

At a shorter height

Overview

The UT6 is an aluminum, corrosion-resistant tower that provides a 6 ft (1.83 m) crossarm height. This general-purpose tower supports the attachment of sensors, mounts, solar panels, antennas, and environmental enclosures. The UT6 includes a lightning and grounding rod, grounding cables, grounding-cable clamps, hinged base, and UV-resistant cable ties. A J-bolt kit is used to secure the base to the concrete pad. This kit is ordered as an option, so it can be ordered separately and shipped before the rest of the tower.

The UT6 is used as a sturdy, long-term instrument mount for a variety of applications. It can be augmented with mounts (for example, CM204, CM220, CM225) that allow attachment of meteorological sensors such as wind sets, pyranometers, and temperature/relative humidity probes. Other meteorological sensors such as barometers, soil temperature and moisture probes, and rain gages can also be used with a UT6-based station.

Benefits and Features

- › Sturdy, long-term instrument mount
- › Shorter height for easier installation
- › Base and grounding kit included

Detailed Description

The tower consists of 2.5 cm (1 in.) OD corrosion-resistant aluminum tubing. In cross-section, it is 25.7 cm (10.1 in.) on a side (center of tubing to center of tubing). It includes an adjustable mast, a hinged base, lightning rod, grounding rod, and cable tie kit.

The J-bolt kit is required to assemble the tower to its concrete pad.

- › The J-bolt kit can be ordered as the -J option, and the kit is delivered with the rest of the tower.
- › If the -NJ option is ordered, without the J-bolt kit, and the kit is ordered separately, the user can have delivery on the J-bolt kit prior to the rest of the tower, making the parts available when the concrete pad is poured.

Specifications

Material	Hardened aluminum
Required Concrete Pad Dimensions	61 x 61 x 61 cm (24 x 24 x 24 in.) Concrete pad requirements assume heavy soil; light, shifting, or sandy soils require a larger concrete pad.
Leg Spacing	26 cm (10.25 in.) between legs, center to center
Pipe Outer Diameter	› 0.953 cm (0.375 in.) for cross support › 2.5 cm (1 in.) for vertical
Crossarm Height (attached to mast)	› 2.7 m (~9 ft) maximum with mast fully extended › 1.5 m (5 ft) minimum › 1.8 m (6 ft) standard

Height	1.83 m (6 ft)
Weight	10.43 kg (23 lb)

Maximum Wind Load Recommendation

-NOTE-

Wind load endurance is affected by quality of anchoring and installation; guy wire tension; soil type; guy angle; and number, type, and location of instruments fastened to the tower.

Wind load recommendation assumes proper installation, proper anchoring, adequate soil, and total instrument projected area of less than 0.19 m² (2 ft²).

Wind Load Recommendation	177 km/h (110 mph) for gusts
--------------------------	------------------------------

For comprehensive details, visit: www.campbellsci.com/ut6 



Campbell Scientific, Inc. | 815 W 1800 N | Logan, UT 84321-1784 | (435) 227-9120 | www.campbellsci.com
AUSTRALIA | BRAZIL | CANADA | CHINA | COSTA RICA | FRANCE | GERMANY | THAILAND | SOUTH AFRICA | SPAIN | UK | USA

© 2019 Campbell Scientific, Inc. | 09/10/2019